

---

# SERVICE INFORMATION LETTER

---

SERVICE INFORMATION LETTER NO. 0195

DATE: June 10, 2026

1. SUBJECT: Handheld Fire Extinguisher Installation
2. MODEL: F-28A, 280, F-28C, F-28C-2, F-28C-2R, 280C, F-28F, F-28F-R, 280F, and 280FX
3. EFFECTIVITY: S/N of helicopters that are registered in countries that recognize approvals granted by EASA and that are equipped with a Halon 1211 fire extinguisher installation.

For all other S/N helicopters equipped with a Halon 1211 fire extinguisher, see paragraph 5.

4. BACKGROUND:

The European Union Aviation Safety Agency (EASA) issued a Certification Memorandum EASA CM No.: CM-CS-013 Issue 01 on June 11, 2025, regarding Halon-free handheld fire extinguisher installations. As confirmed in this Certification Memorandum, Halon-based handheld fire extinguishers were decommissioned as of December 31, 2025. Therefore, Halon 1211 fire extinguishers used on Enstrom helicopters are no longer acceptable for use.

In response to the EASA CM, Enstrom has approved the Halotron BrX fire extinguisher as the replacement for the Halon 1211 fire extinguisher. This Service Information Letter (SIL) informs operators of the fire extinguisher replacement part number and provides instructions for replacing the decommissioned Halon 1211 fire extinguisher.

5. COMPLIANCE:

For Enstrom helicopters registered in a country that recognizes approvals granted by EASA, replace the Halon 1211 fire extinguisher with the Halotron BrX fire extinguisher in accordance with paragraph 6 as soon as practicable.

For all other Enstrom helicopters equipped with the Halon 1211 fire extinguisher, refer to the certifying authority's regulations or guidance regarding the use of Halon-based fire extinguishers. (See references listed in EASA CM No. CM-CS-013 Issue 01, paragraph 4.1.) A Halon 1211 fire extinguisher may be replaced with the Halotron BrX fire extinguisher in accordance with paragraph 6 at owner/operator discretion.

## 6. INSTRUCTIONS:

6.1. Remove the Halon 1211 (model number C352TS) fire extinguisher from its bracket (two-strap (TS) bracket) by opening the two release latches.

6.2. Remove the four screws that attach the fire extinguisher bracket to the back-up plate and remove the bracket.

6.3. Install the Halotron BrX fire extinguisher bracket with the four screws.

NOTE: The bracket design allows for compatibility with the existing back-up plate.

6.4. Position the Halotron BrX (model number A337TS) fire extinguisher into the bracket and engage the two latches to secure the fire extinguisher.

NOTE: The fire extinguisher is properly installed if the neck of the fire extinguisher rests in the bracket and the pressure gauge faces forward.

## 7. PARTS:

Part Number	Description	Quantity
A337TS <sup>1</sup>	Halotron BrX fire extinguisher with two-strap bracket	1
<sup>1</sup> May be procured locally or ordered from Enstrom		

8. SPECIAL TOOLS OR EQUIPMENT: N/A

9. MAN-HOURS: N/A

10. WARRANTY: Per Enstrom policy

11. WEIGHT CHANGE:

	Weight (lb)	Moment Arm (in)	Moment (in-lb)
Halon 1211 (C352TS) Extinguisher	4.59	77.0	353.43
C352TS Bracket	0.50		38.50
<b>Total</b>	<b>-5.09</b>	<b>77.0</b>	<b>-391.93</b>
Halotron BrX (A337TS) Extinguisher	3.01	77.0	231.77
A337TS Bracket	0.65		50.05
<b>Total</b>	<b>+3.66</b>	<b>77.0</b>	<b>+281.82</b>

12. LOG BOOK ENTRY: As necessary for maintenance actions.

13. REPETITIVE INSPECTIONS: N/A